



SHAWNEE COUNTY

REQUEST FOR PROPOSAL

(RFP)

Quotation Number: 055-23

Date Issued: 10-17-2023

Closing Date: 11-03-2023, 2:00pm

Vendor Name: _____

Address: _____

Phone Number: _____

THIS IS NOT AN ORDER

1. In communications, always refer to the above quotation number.
2. All prices and conditions must be shown. Additions or conditions not shown on this bid will not be allowed.
3. Shawnee County reserve the right to accept or reject any part of, or all of, any bid or proposal.
4. All prices quoted are to be less Federal Excise Tax and Kansas Sales Tax.
5. Price quoted shall remain firm for ninety (90) days after bid closing date.

SHAWNEE COUNTY HAS AN ELECTRONIC BID SYSTEM

All vendors are required to create an online portal account (www.snco.us/purchasing) in order to receive or submit bid requests.

ITEM AND DESCRIPTION

Shawnee County is soliciting sealed bids for (1) New/unused 2024 Truck and 60,000 pound Roll-off hoist& bed with auto tarper per the following minimum specifications.

TECHNICAL SPECIFICATIONS

2024 TRUCK CHASSIS:

WARRANTY: 5 yr bumper to bumper and 5 yr-200,000 mile engine (Cummins PP1) including engine after treatment and 5 yr transmission. to include all parts and labor on transmission, rear axles, any internally lubricated parts of diesel engine and including starter, alternator, fuel pump, fuel injectors, turbocharger, water pump, all engine electronics including chassis wiring to and from engine and transmission, modules, relays, solenoid, sensors, chassis wiring, switches, dash gauges, hvac, etc.

ENGINE:

The engine shall be Cummins diesel fueled wet sleeve design with a minimum of 12.5 at 430hp, exhaust brake controlled from a dash mounted switch. The engine shall have a low oil pressure and high engine temperature engine shut down system. The engine must use an S.C.R. system to achieve compliance with E.P.A. 2019 emission standards. The fan will have a Horton two speed air operated clutch. The DEF tank

shall be 11 gallons minimum of usable volume, located on LH side under cab. Exhaust must be RH under cab DPF/SCR w RH SOC vertical tailpipe. Shall have engine mount Powercore air cleaner w/constant torque SS clamps, pop-up air flow restriction indicator. Shall have Immersion engine block heater 120V 1500W with plug under door. Shall have multi-function engine connector for body builder; body builder harness to EOF for customer installed remote throttle control. Shall have 160 amp alternator; must have filter/water separator 12V preheat. Starter shall be 12V electrical system w/centralized power distribution. Batteries shall be 3 PACCAR GP31 threaded post (700) 2100 CCA dual purpose. Battery box shall be cantilever aluminum BOC w/ fiberglass cover. Located on RH side.

WEIGHT:

The unit shall have a total GCW of no less than 60,000 pounds.

WHEELBASE:

The unit shall have a minimum wheelbase of 256"; CA shall have a minimum of 182"; and overall length shall be 384".

AXLES AND SPRINGS:

The unit must have a Dana Spicer D2000 Front axle rated 20k standard track, or approved equivalent. The front springs must have a capacity of not less than 20K with shock absorbers, with maintenance free elastomer spring pin bushings; The unit must have a Dual Dana Spicer D46-170HP rear axle rated at not less than 46,000 pound capacity, with internal lube pump & wheel to wheel differential lockouts, in both rear axles, or approved equivalent. Gear ratio shall be 4.30. The rear suspension shall be Tandem Hendrickson HMX460 46K, have 54" axle spacing, with shocks, track rods, rubber bolster bushings, and heavy duty torque rods, or approved equivalent.

TIRES & WHEELS:

Front: Accuride 22.5 x 12.25 Steel Armor powder coat, hub pilot mount, 5-hand holes. M854 385/65R22.5 18 PR or approved equal. Tandem rear: Accuride 22.5 x 8.25 Steel Armor powder coat, hub pilot mount, heavy-duty 5-hand holes. Bridgestone M843 11R22.5 16 PR or approved equal.

STEERING:

The unit shall have dual power steering gears 20K Sheppard M100P; power steering cooler shall be radiator mounted.

TRANSMISSION:

The unit shall have a push button 6 speed Allison 4500RDS. Shall be limited to 860 lb-ft. Shall include shift control, transmission oil temperature gauge, heat exchanger & oil level sensor. Shall have 3 heavy-duty 2 center bearing driveline. Shall have two steel center bearing cross members installed with heavy duty aluminum gussets replacing standard.

LIGHTS:

2 LED work lights mounted on top rear of cab. 2 LED work lights on the tail light bar on rear of truck. 2 LED amber strobe lights mounted in the tail light bar. 2 LED amber strobe lights mounted in the front bumper.

FRAME & EQUIPMENT:

The unit shall have a heavy duty reinforced frame. Frame rails shall be 10 3/4" x 3 1/2 x 3/8" steel, with full steel inserts. The bumper shall be straight steel, painted channel. Front mud flaps shall be extra wide for use w/ tires that are wide base singles; huck bolts throughout frame where possible. Shall have 90 gallon fuel tank LH under cab. Non-polished DPF/SCR diamond plate with step. Quarter fenders: Black polypropylene

w/ painted steel brackets, single post mounted. Shall have two front mounted forged tow hooks and one rear center mounted forged tow hook or "D" ring, each rated for the weight of the fully loaded truck

BRAKES:

Front brakes shall be 22K Bendix ES S-Cam 16.5x6 in. Drums: 22k lbs, 16.5x6 in Cast, with slack adjusters. Rear dual brakes shall be Bendix 16.5x7 into 46K, with automatic slack adjusters. Bendix ES S-Cam Drums: CastLite. Bendix 6S/6M anti-lock brake system w/air traction control.

Air compressor shall be Cummins 30.4 CFM ISL or approved equivalent, Air dryer shall be Bendix AD-IS Extended Purge heated, or equivalent, to be located inside RH rail BOC; moisture ejection valve w/ pull cable drain.

CAB:

The unit must have aluminum & fiberglass fully hucked conventional cab/ with all aluminum bulkhead doors & continuous stainless steel piano-style door hinges. Shall have cab door bearing blocks, top & bottom. Hood shall be straight unitglas w/ split fenders, with the top factory painted with anti-glare flat black, with radiator mounted grill, mud flaps, & separate bumper. Shall have multi-plex wiring; two spare switches wired to power. Driver seat shall be an air suspension high back with lumbar support and vinyl upholstery with dual armrests. Seat belt shall be gray. Cab heater with integral defrosters & AC 45,000 btu cab heater. Shall have AM/FM/WB/USB radio and Bluetooth. Shall have under dash center console with cup holder & two 12V outlets. Shall have electric LH & RH door locks. Dual mirrors shall be heated & motorized and cowl mounted; 7" x 13" w/ chrome shell; LH/RH convex mirrors 5" x 7". Shall have one single convex mirror 8 1/2" x 4 7/16" located on rider side, non-heated. Shall have two corner & one rear cab stationary windows, NO EXCEPTIONS. Shall have one piece windshield with curved glass. Shall have exterior aerodynamic sun visor w/ integral marker lights; 2" rubber wheel well fender extension; severe service reinforcements for aluminum cab sill; and Link Cabmate suspension. Shall have extended life halogen headlamps; electric backup alarm. Shall have adjustable telescoping tilt steering column. The instrument panel shall have speedometer, tachometer, fuel gauge, engine coolant temperature gauge, engine oil pressure, voltmeter, primary & secondary air reservoir gauges & air application gauge. Shall have engine oil temperature gauge w/ integral warning light, and fuel filter restriction gauge. DEF level gauge and warning lamp; engine hour meter and outside air temperature readouts. Shall have self cancelling turn signals w/column mounted headlight dimmer switch & intermittent wiper control. Shall have LED turn signals mounted on fender; LED stop, turn, tail: flange mounted with two LED backup lights and with and LED license plate. Shall have dual flush floodlights; marker lights mid frame & reflectors mounted standout. Shall have cab access grab handles LH/RH, inside doorframe above dash, and long grab handles RH/ LH side of cab. Shall have daylight door: LH/RH included RH peeper window. Shall have bug screen mounted front of grille. Shall have firewall mounted HVAC system for accessibility.

PAINT:

DuPont Imron Polyurethane Enamel Orange (Spectra Master Yellow)

WARRANTY:

Warranty pricing MUST reflect pricing for a chassis to be used in a refuse application. Warranties that are misquoted for use in a non refuse application and are not of adequate coverage according to the Original Equipment Manufacturer shall become the financial responsibility of the vendor.

SERVICE:

The vendor shall give any information as to how long they have been involved with the product, and how they plan to support the vehicle after delivery. Give hours of operation, mobile phone numbers for after hour services and describe parts and services available. Warranty repair facility shall be within 75 mile radius.

TECHNICAL SPECIFICATIONS – ROLL-OFF HOIST – OUTSIDE RAIL 60,000 LBS

HOIST FRAME:

The hoist shall carry a manufacturer's rated capacity of 60,000 lbs. and shall be capable of carrying a 22-foot container platform.

The minimum hoist frame-to-ground angle shall be 47 degrees from horizontal when the hoist frame is in the full raised position.

The hoist frame shall have a tail roller constructed of schedule 80 steel pipe supported on each side by a press-fit 3" wide cast roller bearing mounted on a 2" steel shaft.

Hoist main rails shall be designed and spaced to receive containers with a longitudinal spread of 36" minimum and 38" maximum inside dimension so as to straddle the hoist frame rails.

Hoist main rails must be constructed of 4" x 8" x 1/2" wall A-500 grade 'C' tubing. Lesser strength grade 'B' or 'A' tubing is not acceptable.

The hoist shall rest on, and pivot from, a sub-frame constructed of 4" x 2" x 1/4" wall A-500 grade 'C' tubing. Lesser strength grade 'B' or 'A' tubing is not acceptable.

The forward end of the frame structure shall be equipped with 1 vertical 10" sheave with a bronze bushing. The sheave shall rotate on a 2" diameter heat-treated steel pin with grease zerk fitting for lubrication.

The hoist frame shall include front container stops of 1 1/2" steel plate with a locking device that is actuated when the container is in the full forward position and the hoist is in the lowered position.

The rear hinge pins shall be not less than 3" heat-treated steel.

TECHNICAL SPECIFICATIONS – ROLL-OFF HOIST – TARP SYSTEM

MOUNTING:

The tarp system shall be mounted to the chassis and hoist body. The mounting shall be by 3" x 3" x 3/16" tubing.

The slide tubes for the tarp arm pivots shall be 3 1/2" x 3 1/2" x 1/4" tubing.

The gantry shall be mounted to the chassis by formed angles of 3/8" plate with two gussets of 3/8" plate per side.

GANTRY:

The gantry shall be capable of being extended 48" vertically by a 2" x 48" double acting hydraulic cylinder.

The gantry extension tubes shall be a 3 1/2" x 3 1/2" x 3/16" tube housed in a 4" x 4" x 3/16" tube.

TARP:

The tarp shall be heavy nylon mesh with a solid 18 oz vinyl reinforcement on all sides. A full width reinforcement of 54" across the front and 72" across the rear to protect the tarp from wear.

TARP ARMS:

Pivoting arms shall be of a three piece design. (Must Have Pioneer Rack And Pinion Strong Arm Tarp System)

Arms shall be constructed of 1 1/2" x 3" x 3/16" tubing with a second 1 1/2" x 3" x 3/16" tube from the pivot to the cylinder mount.

The arms shall be pivoted by one cylinder per side. The cylinders shall be rephasing cylinders in a master and slave configuration so both arms are synchronized in operation.

The master cylinder shall be 3" dia. x 30" stroke. The slave cylinder shall be 2 1/2" dia. x 30" stroke.

TARP ADJUSTMENT FOR CONTAINER:

The cover shall be adjusted for the container length by moving the pivot for the arms on a slide tube.

Tarp controls inside the cab and outside also.

The mounts shall be slid by one cylinder per side. This will be done with rephasing cylinders in a master and slave configuration so that both sides move the same distance.

The master cylinder shall be 3" dia. x 42" stroke. The slave cylinder shall be 2 1/2" dia. x 42" stroke.

HYDRAULIC SYSTEMS:

PTO shall be for front engine PTO off of crank shaft with adaptor and mounting hardware.

Hydraulic power shall be by a gear type hydraulic pump with a 3 g.p.m. priority flow divider valve plumbed into the hydraulic system for the roll-off hoist.

The three spool control valve shall have a 5 g.p.m. capacity bypass pressure relief valve, factory set at 2500 PSI.

Electric Hydraulic tank heater. If any questions please call William Owens at (785) 806-0651

Hydraulic hoses shall be abrasion resistant material.

Controls for the valve shall be located street-side adjacent to the driver's door. Also shall have controls inside the cab to operate hoist. Shall have a (Functioning) speed up control inside the cab and outside the cab.

PAINT FINISH:

Complete unit shall be cleaned with all weld slag removed.

The finish coat color shall be standard factory black to match the truck frame.

MOUNTING:

All tarper installation shall be done by either the manufacturer at said manufacturer's place of business or at an authorized dealer's location.

Mounting shall be to chassis and tilt frame manufacturer's engineering specifications.

OPERATING MANUALS:

One complete set of Maintenance, Service and Repair manuals or CD-Rom of each for chassis and the cab & also roll-off bed & auto tarper.

SERVICE:

The vendor shall give any information as to how long they have been involved with the product, and how they plan to support the vehicle after delivery. Give hours of operation, mobile phone numbers for after hour service and describe parts and services available.

GENERAL SPECIFICATIONS

PRE-DELIVERY SERVICE:

The truck and all components shall be free of leaks and fully operational with all adjustments made prior to delivery.

REPAIR AND PARTS MANUALS:

Supplier shall furnish two sets of repair and parts manuals on a Thumb Drive for the truck and controls.

TECHNICAL SERVICES:

Supplier shall provide the services of a competent technician thoroughly trained in the use, operation and preventive maintenance for a period of one working day.

WARRANTIES:

The unit as specified and all equipment, standard and optional, shall be completely assembled, adjusted, installed and ready for use on a truck chassis furnished by others. Bidder shall provide a (5) year warranty on hydraulic cylinders, (5) year warranty for defects in materials and workmanship parts and labor from date of delivery including wiring and electrical components wired in or connected to chassis or transmission or engine system shall be covered for five (5) years parts and labor.

DELIVERY:

Delivery shall be within 180 days from the date a purchase order is issued to the winning bidder. Delivery shall be to: Shawnee County Solid Waste Maintenance Shop, 1515 NW Saline Street; Topeka, Kansas.

LIQUIDATED DAMAGES:

Owner and Vendor recognize that time is of the essence of this Agreement and that Owner will suffer financial loss if the Equipment is not completed / delivered within the time specified. They also recognize the delays, expense and difficulties involved in proving in legal proceedings the actual loss and increased maintenance costs suffered by Owner if the equipment is not completed and delivered on time. Accordingly, instead of requiring any such proof, Owner and Vendor agree that, as liquidated damages for delay (but not as a penalty), Vendor shall pay Owner: \$ 50.00/calendar day/vehicle for each calendar day beyond the 180-day delivery period that a vehicle is not received by Owner at the location listed above.

BID RESPONSE

BID RESPONSE:

The bid response shall include complete warranty/product support information, including printed manufacturing specifications, published literature, and photos or illustrations of units that the bidder proposes to furnish.

EXCEPTIONS:

Any exceptions or variances to the exact bid specifications stated herein shall be listed on a separate page clearly marked "Exceptions:" **Failure to do so may result in rejection of the bid.**

BID EVALUATION:

The County reserves the right to reject any bid. Bid evaluation criteria will include, but not be limited to the following:

1. Compliance to bid specifications
2. Purchase price
3. Owner's experience with performance of manufacturer's equipment and after purchase service
4. Location of nearest dealer/repair facility
5. Warranty terms
6. References on performance of manufacturer
7. Design and quality of construction
8. Financial stability of manufacturer

If additional information is required, **please submit questions through the online bid portal.**

PLEASE SUBMIT ATTACHMENT 1 AS THE FIRST PAGE OF YOUR BID

BID RESPONSE

Closing Date: Bids will be received until 2:00 p.m. CDT on the scheduled closing date. The online bid portal will not accept any new bids after this time.

Signature of Bids: Each bid must show in the space provided the complete business or mailing address of the bidder and must be signed by him/her with his/her usual signature.

Withdrawal of Bids: Bids already submitted may be withdrawn on the Electronic Bid System or upon proper identification of bidder and provided request is received prior to time of closing. Negligence on the part of the bidder in preparing the bid confers no right for the withdrawal after the time set for closing of bids.

Register Your Company: For a *mandatory* pre bid meeting, you *must* be registered in our bid portal for us to record you as an attendee. If you are not marked as attended, the system will not allow you to download a bid. It will also stop you from downloading your bid if you are not registered. Also, you will need to subscribe to the bid types you can provide. This will automatically send you bid requests in the future.

Please Submit Your Bids Early: In case you have problems getting your bid to upload and need assistance, we suggest you submit before 1:30 pm. Please contact us at once if you have issues uploading. Our system will not allow any bids to be uploaded after 2:00 pm. If your pricing changes, you can replace your bid in the system any time before the 2:00 closing.

Bid Openings: All bids submitted before the specified bid closing time shall be opened and properly recorded on the bid tabulation sheet. Subsequent to the bid opening, all bids shall be thoroughly evaluated and a determination made as to their compliance with applicable specifications. The appropriate County department head shall make this determination. Upon completion of the above determination, an analysis of all bids submitted shall be prepared and formally presented to the Board of County Commissioners for acceptance and approval of the lowest and/or best bid. The Board of County Commissioners reserves the right to accept or reject any and/or all bids and to waive any irregularities or informalities therein.

Notice to Successful Bidders: The successful bidder will be notified by email or telephone as soon as possible after bids have been opened, tabulated, and analyzed.

Notice to Unsuccessful Bidders: Unsuccessful bidders will not be notified.

DEMANDSTAR POSTINGS

Demandstar Website: Shawnee County open projects are posted on Demandstar as a secondary posting. Demandstar tracks broadcast and plan holder data. Bids must be submitted through the Shawnee County Bid Portal.

Shawnee County Bid Portal: When an open project is posted, Shawnee County is not able to track who downloads project information off the bid portal website. Bids must be submitted through the Shawnee County Bid Portal to be considered. All projects are posted on the County website, not all projects are posted on the Demandstar website. Registration is free.

TERMS AND CONDITIONS

In the event that goods or services delivered by the vendor are unsatisfactory and remain unsatisfactory after a notice and an opportunity to correct the deficiencies, the County reserves the right to purchase substitute goods or services from the other bidders.

Shawnee County reserves the right to negotiate separately with any vendor after the opening of this RFP when such action is considered in its best interest. Subsequent negotiations may be conducted, but such negotiations will not constitute acceptance, rejection or a counteroffer on the part of the County.

Shawnee County interprets the term “lowest responsible and best bidder” as requiring Shawnee County to:

- A. Choose between the kinds of materials, goods, wares, or services subject to the proposal, and
- B. Determine which proposal is most suitable for its intended use or purpose. Shawnee County can consider among other factors such things as labor cost, service and parts availability and maintenance costs of items upon which proposals are received. Shawnee County can determine any differences or variations in the quality or character of the material, goods, wares or services performed or provided by the respective vendors.

Shawnee County will award the bid. If the successful vendor refuses or fails to make deliveries of the materials/services within the times specified in the RFP, purchase order or contractual agreement, Shawnee County may by written notice, terminate the contract OR purchase order. The successful vendor will certify and warrant that goods, personal property, chattels, and equipment sold and delivered are free and clear of any and all liens, or claims of liens, for materials or services arising under, and by virtue of the provisions of K.S.A. 58-201, et seq., and any other lien, right, or claim of any nature or kind whatsoever.

The vendor hereby certifies that he or she has carefully examined all of the documents for the project, has carefully and thoroughly reviewed this RFP, understands the nature and scope of the work to be done; and that this proposal is based upon the terms, specifications, requirements and conditions of the RFP, and documents. The vendor further agrees that the performance time specified is a reasonable time, having carefully considered the nature and scope for the project as aforesaid.

Shawnee County will use discretion with regards to disclosure of proprietary information contained in any response, but cannot guarantee the information will not be made public. As a governmental entity, Shawnee County is subject to making records available for disclosure pursuant to the Kansas Open Records Act. Any confidential or proprietary information should be clearly marked.

Shawnee County reserves the right to enter into agreements subject to the provisions of the Cash Basis Law (K.S.A. 10-1112 and 10-1113), the Budget Law (K.S.A. 79-2935). Agreements shall be construed and interpreted so as to ensure that the County shall at all times stay in conformity with such laws, and as a condition of agreements the County reserves the right to unilaterally sever, modify, or terminate agreement at any time if, in the opinion of its legal counsel, the Agreement may be deemed to violate the terms of such law.

The vendor certifies that this proposal is submitted without collusion fraud, or misrepresentation as to other vendors, so that all proposals for the project will result from free, open, and competitive proposing among all vendors.

This RFP, responses thereto and any contract documents will be governed by the law of the State of Kansas. Any dispute arising out of the same will be litigated only within the courts of the State of Kansas.

Vendor agrees that all data, documents, and information, regardless of form that is generated as a result of this RFP are the property of Shawnee County. The County shall not be liable to reimburse any vendor for the costs of creating, compiling or delivering the same to the County.

By submission of a response, the proposer agrees that at the time of submittal, it: 1) has no interest (including financial benefit, commission, finder's fee, or any other remuneration) and will not acquire any interest, either direct or indirect, that would conflict in any manner or degree with the performance of proposer's services, or 2) benefit from an award resulting in a "Conflict of Interest." A "Conflict of Interest" will include holding or retaining membership, or employment, on a board, elected office, department, division, or bureau, or committee sanctioned by and/or governed by the Board of Shawnee County Commissioners of the County of Shawnee, Kansas. Proposers will identify any interests, and the individuals involved, on separate paper with the response and will understand that the County may reject their proposal at its sole discretion.

No gifts or gratuities of any kind shall be offered to any County employee at any time.

The Proposer certifies that this proposal is submitted without collusion, fraud, or misrepresentation as to other Proposers, so that all proposals for the project will result from free, open, and competitive proposing.

The County is exempt from the payment of Federal and excise taxes and from Kansas sales tax.

Vendor credit agreements are prohibited. Unless otherwise stated in this document, payment will be made from vendor-submitted invoice(s) via ACH transfer, check, or credit card, net 30 days. Shawnee County will not complete any credit application or agree to credit terms supplied by vendor.

Nondiscrimination: Shawnee County is committed to the concept of equal employment opportunity. All bidders and contractors are expected to comply with the provisions of K.S.A. 44-1030 and 44-1031, copies of which are attached and shall be a part of this contract and other applicable Federal and Kansas laws governing equal employment opportunity.

In accordance with K.S.A 44-1030, vendor hereby agrees to the following:

- A. He or she will observe the provision of the Kansas Commission on Human Rights and will not discriminate against any person in the performance of work under the present contract because of race, religion, color, sex, national origin, ancestry, or physical disability.
- B. In all solicitations or advertisements for employees, he or she will include the phrase, "Equal Opportunity Employer", or a similar phrase to be approved by the Kansas Commission on Human Rights.
- C. If he or she fails to comply with the manner in which he or she will be deemed to have breached the present contract, and it may be canceled, terminated, or suspended, in whole or in part, by Shawnee County, Kansas.
- D. If he or she is found guilty of a violation of the Kansas Act Against Human Rights under a decision, or order of the Kansas Commission on Human Rights which has become final, he or she will be deemed to have breached the present contract, and it may be canceled, terminated, or suspended, in whole or in part, by Shawnee County, Kansas; and,
- E. He or she will include the provisions of subsections (a) through (d) inclusively of this paragraph in every subcontract or purchase order so that such provision will be binding upon such subcontractor or vendor.

Provisions of K.S.A. 44-1030 Statute:

Mandatory provisions applicable to contracts of the state and other political subdivisions; cancellation, when; application to subcontract; non-application to certain contract. (a) Except as provided by subsection (c) of this session, every contract for or on behalf of the state or any county or municipality or other political subdivision of the state or any agency of or authority created by any of the foregoing, for the construction, alteration or repair of any public building or public work or for the acquisition of materials, equipment, supplies or services shall contain provisions by which the contractor agrees that:

- 1. The contractor shall observe the provisions of the Kansas act against discrimination and shall not discriminate against any person in the performance of work under the present contract because of race, religion, color, sex physical handicap unrelated to such person's ability to engage in the particular work, national origin or ancestry.
- 2. In all solicitations or advertisements for employees, the contractor shall include the phrase, "equal opportunity employer," or a similar phrase to be approved by the commission.
- 3. If the contractor fails to comply with the manner in which the contractor reports to the commission in accordance with the provisions of K.S.A. 44-1032, the contractor shall be deemed to have breached the present contract and it may be cancelled, terminated or suspended, whole or in part, by the contracting agency.
- 4. If the contractor is found guilty of a violation of the Kansas act against discrimination under a decision or order of the commission which has become final, the contractor shall be deemed to have breached the present contract and it may be cancelled, terminated or suspended, in whole or in part, by the contracting agency.
- 5. The contractor shall include the provisions of paragraphs one (1) through four (4) inclusively of this subsection (a) in every subcontract or purchase order so that such provisions will be binding upon such

subcontractor or vendor. (b) The Kansas commission on civil rights shall not be prevented hereby from requiring reports of contractors found to be not in compliance with the Kansas act against discrimination. (c) The provisions of this section shall not apply to a contract entered into by a contractor: (1) Who employs fewer than four (4) employees during the term of such contract; or (2) Whose contracts with the governmental entity letting such contract cumulatively total five thousand dollars (\$5,000) or less during the fiscal year of such governmental entity.

Provisions of K.S.A. 44-1031 Statute:

Same; personnel to be used in performing contracts; reports; non-application to certain contractors. Every person, as defined in subsection (a) of K.S.A. 44-1002, who wishes to enter into a contract which is covered by the provisions of K.S.A. 44-1030 shall upon request of the commission, inform the commission in writing of the manner in which such person shall recruit and screen personnel to be used in performing the contract. The report shall be made on forms to be supplied by the commission. The provisions of K.S.A. 44-1030 and of this section shall not apply to any contractor who has already complied with the provisions of such sections by reason of holding a contract with the federal government or a contract involving federal funds.

History: L.1972, ch.184, & 15; L. 1975, ch. 264, & 8; L. 1977, ch. 183, & 2; July 1.

All questions regarding this bid should be posted on the online Electronic Bid System.

For problems with the online Electronic Bid System, please contact:

Shawnee County Audit Finance Department

e-mail: Auditfinance@snco.us phone: (785) 251 – 4039

The undersigned agrees with all terms and conditions stated above:

Signature	_____
Printed Name	_____
Title	_____
Email Address	_____
Phone Number	_____

ATTACHEMENT 1

Quotation Number: 055-23
Date Issued: 10-17-2023
Closing Date: 11-03-2023, 2:00pm

Vendor Name: _____

SCHEDULE OF PRICES

ITEM	QUANTITY	UNIT PRICE
2024 Heavy-duty Roll off Truck Chassis & hoist with auto-tarper	1	\$ _____

State Make and Model of Truck Chassis

State Make & Model of Roll-Off Hoist Unit

TRADE-IN VEHICLE:

SW4005 (Roll Off) 2018 International HV613 **Eng:** Navistar A26 **Mil:** 120,946 **Body:** Galbreath
Roll Off Bed 60,000lb Outside Rail Roll Off Hoist **Ser #** U5-OR-174 (Tarper) - Pioneer Rack and
Pinion Model RP4500 **VIN#** 3HTESTZTXKN36012

Subtotal Trade-in Allowance: \$ _____

TOTAL BID PRICE
(i.e., Subtotal Bid Price minus Subtotal Trade-in Allowance) \$ _____

TOTAL BID PRICE (Printed in words)

SHOW TERMS _____

DELIVERY WILL BE MADE _____

F.O.B. _____

PHONE NO. _____

E-MAIL. _____

COMPANY or FIRM NAME

BY: _____

DATE: _____

